City of Trussville, Alabama Gas Permit Application

Gas Permit #	s Permit # Building Permit #							
Job Address								
Owner or Occupant								
Type of Occupancy	Work To Be Doi	ne In		Wate	r Heater			
□ Residential□ Commercial□ Other	 New Building □ Building Addition □ Existing Building □ Pressure Test □ Other 		Tank	Existing (□ Electri □ Gas □ LP	С			
Description of Work								
ENGINEERED DRAWINGS AR STORAGE WATER HEAT INSTANT WATER HEAT OTHER	Gas Fixtures (Lis	t number of Ea	ach Fixtu		LOG	LIGHTER		
CONTRACT COST \$		PERMIT FEE	\$					
COMPANY NAME								
Address								
Street	Sta	ate ZIP Cod	e Phor	ne#	E-Mail			
Card Holder's Name			Master Gas Fitter Card No					
I hereby certify that I have read the comply with all City Ordinances an agent for the herein described wor	d State Laws regulating go	-				_		
Print Name	D	ate	Sigi	nature				

City of Trussville, Alabama Gas Permit Application

The purpose of this list is to make you aware of some of the new construction requirements contained in the International Residential Building Code (IRC) as adopted by the City of Trussville. Please be aware that this list is not all inclusive and does not diminish the importance of those changes not covered.

- G2411.1 Pipe and tubing other than corrugated stainless steel tubing (CSST) that is likely to become energized is required to be electrically continuously bonded to an effective ground-fault current path.
- 2. G2412.5 Identification. For other than steel pipe, exposed piping shall be identified by a yellow label marked "GAS" in black letters. Their marking shall be spaced at intervals not exceeding 5 feet.
- 3. G2406.2 Appliances shall not be located in sleeping rooms, bathrooms, toilet rooms, storage closets or surgical rooms, or in a space that opens only into such rooms or spaces. There are some exceptions. See inspector.
- 4. G2408.2 Equipment and appliances having an ignition source shall be elevated such that the source of ignition is not less than 18 inches above the floor in hazardous locations and public garages, privet garages, repair garages, motor fuel-dispensing facilities and parking garages.
- 5. G2419.4 Sediment traps shall be installed downstream of the appliance shutoff valve as close to the inlet of the appliance as practical. The sediment trap shall be either a tee fitting having a capped nipple of any length installed vertically in the bottom-most opening of the tree.
- G420.5.3 Where the appliance shutoff valve is installed at a manifold, such shutoff valve shall be permanently identified.
- 7. G2415.7 Above ground piping outdoors. All piping installed outdoors shall be elevated **not** less than 3 ½ inches above ground.
- 8. G2415.10 Minimum burial depth. Underground piping systems shall be installed a minimum depth of 12 inches below grade.

SIGNATURE	DATE	
-		